

# Airless Spray Equipment For Single-Component Protective Coatings



# Graco Has You Covered

Whether it's a large coating project like a bridge, ship or tank, or a simple touch-up project that only takes a few hours, you depend on your spray equipment to deliver a flawless performance every time. Graco offers a complete lineup of the industry's most dependable single-component sprayers—in the exact size you need to accomplish any airless spray project.

## **Reduce your cost of ownership with Graco**

Rugged, durable and dependable, Graco sprayers are built to last. They can easily handle the industry's toughest high solids, 100% solids and solvent-free coatings—even in the most severe conditions. Because Graco pumps are constructed with long-lasting parts and the highest quality materials, you gain productivity and spend less downtime on maintenance. Which means you can complete your projects faster and more efficiently.

		7				
			90	0		0 10
	HOW TO CHOOSE YOUR SPRAYER	XForce™ HD	Merkur <sup>®</sup> X48 / X72	Xtremo	e° NXT°	Xtreme <sup>®</sup> XL
	HOW LARGE IS YOUR PROJECT?  Typical Applications*	Touch-up and spot repair	Smaller projects that require power and portability	Medium to large projects	Large projects	Large projects that require continuous duty or multi-gun
	WHAT IS THE REQUIRED MATERIAL OUTPUT? Output Range at 60 Cycles/min, gpm (lpm)	.0967 (.33-2.54)	.8-1.2 (3.0-4.5)	1.5-3.4 (5.7-12.9)	2.3-4.6 (8.7-17.4)	3.4-6.7 (12.9-25.4)
	WHAT IS THE DUTY CYCLE OF THE SPRAYER? Production	Touch-up	Low-Med	Med-High	High	Very High
	HOW MANY CREW MEMBERS CAN SPRAY FROM ONLY ONE UNIT?	1	1	1	1–2	Multiple 1–6**
	Motor Type	HD Brushless	NXT 1800	NXT 3400	NXT 6500	XL 10000
	Motor Diameter, in (mm)	N/A	7.5 (190)	7.5 (190)	10.375 (263)	13 (330)
	Motor Displacement, cc/stroke	N/A	1800	3400	6500	10330
L	Working Pressure, psi (bar)	1000 – 4000 (69 – 276)	4800, 7200 (331, 496)	3150 – 7250 (217 – 496)	4550 – 7250 (314 – 496)	4800-7250 (331-496)

<sup>\*</sup> General guidelines only. Please consult your Graco distributor to ensure you order the proper sprayer for your application.

<sup>\*\*</sup> Depending on spray tip size and material.



# Xtreme® XL Series

Designed with the new XL Air Motor, the Xtreme XL Sprayer can run up to six guns in a high-output environment with virtually no pulsation or pattern fluctuation. The efficient design includes advanced features that ensure superior performance, even in oily, dirty and wet air environments.



#### **Exposed Poppets**

· Easy access for service and troubleshooting

#### 10,000 cc XL Air Motor

- For 45:1, 70:1, 80:1, 95:1 sprayers
- 13 in (330 mm) diameter
- · Air-piloted for sharp changeovers
- · Low pulsation, even with multiple guns

#### De-Ice Bleed Air Control

 Maintains performance during heavy icing conditions

#### Manual Shuttle Override Button

 Allows manual restart of air motor if main valve experiences ice buildup

#### External Pilot Lines

- Isolate lines from cold valve body
- Eliminates non-restartable icing stalls

#### Simplified Valve Design

- · Fewer components for easier serviceability
- Little to no pulsation or pattern fluctuation, even with multiple guns
- Quiet operation, even compared to smaller motors

#### **Xtreme Lowers**

- Field-proven
- Easy to maintain
- · Quick knockdown


S		XL45*	XL70	XL80	XL95
XL SPRAYER Specifications	Output per cycle (cc)	430	290	250	220
PRA	Maximum Working Pressure, psi (bar, MPa)	4800 (331, 33.1)	7250 (500, 50.0)	7250 (500, 50.0)	7250 (500, 50.0)
XL 8	Maximum Air Input Pressure, psi (bar, MPa)	100 (7 .07)	100 (7 .07)	88 (6.1, .61)	76 (5.2, .52)
S	Output at 60 Cycles/min gpm (lpm)	6.7 (25.4)	4.6 (17.4)	4 (15.1)	3.4 (12.9)


<sup>\*</sup> Uses Dura-Flo™lower

## **High Pressure and High Flow**

Even at high cycle rates, the Xtreme XL Sprayer maintains the high pressure needed to effectively spray up to six guns.


Compare the difference in pressure drop and pulsation between the Xtreme XL Sprayer and a competitive brand sprayer at high flow rates.






- A 500 psi (34.5 bar) dynamic pressure drop
- An 1,800 psi (124 bar) dynamic pressure drop
- Little to no perceivable pulsation
- D Slow changeover means pulsation and pattern fluctuation

# **Ordering Information**





## Heavy-fluid, high pressure spray packages

Designed for materials that will gravity feed, but are higher viscosity and filled, requiring a filter-less pump lower for less plugging.

Packages include 10 gal (38 L) SST hopper, no fluid filter, ¾ in. outlet check valve, ¾ in. x 50 ft. (15 m) hose, ½ in. x 25 ft (7.6 m) whip and XHF spray gun with 429 tip.

24X593 XL70 Heavy-fluid\* spray package

24X594 XL80 Heavy-fluid\* spray package

\* Heavy-fluid materials vary and should be tested with a qualified distributor. Material should be pourable and self-leveling.

## **Optional Accessories**

24X570\* 10 gal (37.8 l), stainless steel

hopper with fittings for mounting

16U536 10 gal (37.8 l), stainless steel hopper without fittings

24X547 Hopper adapter kit for XL45

262826 Gun splitter

24X553 3/4 in hose to high flow gun kit

24X550 DataTrak Control

with runaway solenoid

24X552 DataTrak Control without runaway solenoid

\*Adapts to XL Sprayers only

For more information on Parts & Accessories for High Pressure Protective Coatings Equipment, see brochure 349329.

# Xtreme NXT Series


The Xtreme NXT series of airless sprayers are built to handle the toughest protective coatings and corrosion control applications. The Xtreme NXT also provides a smooth, rapid changeover, which minimizes pulsation, decreases user fatigue and achieves a more consistent finish. It offers a modular design for convenient maintenance, a de-icing feature and reduced noise level.




		Xtreme NXT 3400 Packages			
		X30	X40	X55	X80
S E	Output per cycle	220cc	180cc	115cc	85cc
RAY	Motor Size	NXT 3400	NXT 3400	NXT 3400	NXT 3400
XTREME SPRAYER SPECIFICATIONS	Maximum Working Pressure, psi (bar, MPa)	3150 (217, 21.7)	3800 (262, 26.2)	5950 (410 41.0)	7250 (500, 50.0)
XTRE	Maximum Air Input Pressure, psi (bar, MPa)	100 (7, .07)	100 (7, .07)	100 (7, .07)	100 (7, .07)
	Output at 60 Cycles/min gpm (lpm)	3.4 (12.9)	2.9 (11)	2 (7.6)	1.5 (5.7)

Xtreme NXT 6500 Packages						
X45	X50	X60 X70		X90		
290cc	250cc 220cc		180cc	145cc		
NXT 6500	NXT 6500	NXT 6500	NXT 6500	NXT 6500		
4550 (313, 31.3)	5200 (359, 35.9)	6000 (417, 41.7)	7250 (500, 50.0)	7250 (500, 50.0)		
100 (7, .07)	100 (7, .07)	100 (7, .07)	100 (7, .07)	80 (5.5, .55)		
4.6 (17)	4.0 (15.2)	3.4 (12.9)	2.9 (11)	2.3 (8.7)		

# **Ordering Information**





## **Special Package Configurations**

#### Xtreme Zinc Packages

Special zinc circulation system keeps particles in suspension, making zinccoating applications easier.

Has standard Xtreme lower with no filter and de-icing NXT Air Motor.



## Xtreme Air Assisted Packages

Combines airless atomization speed with the fine finish of air spray. Ideal for high production, smooth finish applications. Includes De-Icing NXT Air Motor.

287975 30:1 Heavy-Duty Cart AA Package (G40 Spray Gun and Hoses)

287976 40:1 Heavy-Duty Cart AA Package (G40 Spray Gun and Hoses)

## High Flow Dura-Flo Packages

Include De-Icina NXT Air Motor.

287980 23:1 Sprayer Package with a Dura-Flo 580 cc lower plus DataTrak (Silver Spray Gun and Hoses)

287979 23:1 Sprayer Package with a Dura-Flo 580 cc lower

287981 32:1 Sprayer Package with a Dura-Flo 430 cc lower (Silver Spray Gun and Hoses)

## Packages without Lowers

XN3DH2 NXT 3400 De-Icing with DataTrak on a Bare Heavy Duty-Cart \*

XN3DH4 NXT 3400 De-Icing on a Bare Heavy-Duty Cart \*

XN3DL2 NXT 3400 De-Icing with DataTrak on a Bare Lightweight Cart \*

XN3DL4 NXT 3400 De-Icing on a Bare Lightweight Cart \*

XN6DH2 NXT 6500 De-Icing with DataTrak on a Bare Heavy-Duty Cart \*

XN6DH4 NXT 6500 De-Icing on a Bare Heavy-Duty Cart \*

XN6DL2 NXT 6500 De-Icing with DataTrak on a Bare Lightweight Cart \*

XN6DL4 NXT 6500 De-lcing on a Bare Lightweight Cart \*

247312 Cart adapter for NXT2200 Air Motor

#### Carts

287919 Lightweight base cart

287884 Heavy-duty base cart

287971 25:1 Heavy-Duty Cart Zinc Package, no hose or gun

287972 40:1 Heavy-Duty Cart Zinc Package, no hose or gun

287973 25:1 Heavy-Duty Cart Zinc Package (Silver Spray Gun 238591 and Hoses)

287974 40:1 Heavy-Duty Cart Zinc Package (Silver Spray Gun 238591 and Hoses)

Pictured: Xtreme Zinc Package with Circulation and Heavy-Duty Cart

<sup>\*</sup> Add any Xtreme Lower (Sizes 145cc-290cc) to make a Package. Includes tie rods, coupling kit and a suction hose.

# Merkur X48 and X72

Merkur X48 and X72 single component airless sprayers offer the ultimate combination of power and portability, giving you the ability to spray tough materials in the most challenging situations. Weighing just 99 pounds (45 kg), the Merkur Sprayer can easily be positioned in tight areas, without sacrificing spray quality or power.

#### High Pressure

- With up to 7200 psi (500 bar, 50 MPa)
- · Sprays high solids coatings
- Supports longer hose runs

#### Easy to Maintain

· Easy to disassemble pump from air motor

#### Throat and Piston Packings

· Self-adjusting and spring loaded to maintain packing life

#### Pressure Bleed Valve

- Floating ball design zero cavity
- · Reduces clogging and leaking

#### Merkur Pump Lower

- · Improved handling of high viscosity coatings
- Long-lasting Chromex™ coated rod

#### Inlet

• Smooth 1-1/4 in inlet reduces "dead spots" and coating buildup

#### Quick Knock-Off Suction Hose

• Large 1 in x 6 ft (25.4 mm x 1.8 m) suction hose

## Lightweight and Portable

• Weighs only 99 lb (45 kg)



Maximum Fluid Working Pressure, psi (bar, MPa) Recommended Tip Size Fluid Flow at 60 Cycles/min gpm (lpm) Pump Weight, lb (kg)

<sup>\*</sup> Varies by coating and duty cycle



16V175 Merkur X48 bare unit

16U920 Merkur X48 complete package

#### **Accessories**

16U924 Repair kit, X72 fluid section

16U925 Repair kit, X48 fluid section

224459 60 mesh fluid filter element, 2-pack

224468 100 mesh fluid filter element, 2-pack

106149 Air line filter kit, ½ in npt (fbe), 20 micron (requires fittings)

24A576 Optional DataTrak™ Kit

Complete package includes XTR gun with 519 tip and 3/8 in x 25 ft (7.6 m) hose, 6 ft (1.8 m) whip

# XForce HD Heavy-Duty.

The XForce HD heavy-duty cordless sprayer is the industry's first cordless airless sprayer designed to spray the toughest protective coatings and corrosion control materials. It's an easy solution for touch-ups, spot repairs or small areas.

#### **HD Brushless Motor**

- · Delivers the highest performance and longest life
- 1000-4000 psi (69-276 bar)

#### FullFlo Pressure Control

- Fully adjustable to achieve the finish you need
- · Optimized for both thick and thin coatings
- · Easy to read dial

## Standard RAC X™ SwitchTip™ and Guard

- · Accepts standard Graco RAC tips, guards and extensions
- Easy Out™ Tip Filter keeps spraying with fewer tip plugs
- Supports .009-.025 tips

#### Easy Out Tip Filters

- · Designed to decrease tip plugging
- Available in 30, 60 or 100 mesh sizes
- Thread-less design for easy removal

#### Spray-N-Throw Cup System

- Disposable 44 oz. (1.3 l) lid and liner system virtually eliminates cleanup
- Sealed cup protects material while minimizing spills
- Spray at an angle even upside down

#### 28V High Power Lithium-Ion Power Packs

- Designed for maximum power to spray the most demanding materials
- Able to spray up to 1 gal (3.78 l) per battery charge

#### **Ground Strap**

• 25 ft (7.6 m)

## Sprayable materials

- High solids epoxy primers and coatings up to 100% solids content
- · Solvent-borne coatings
- Water-borne coatings
- · Fire retardant coatings

- High solids polyurethane top coatings
- Plural component coatings
- Elastomerics



# **Ordering Information**

16N654 Complete kit with RAC X 517 tip and 30 mesh filter

# **Count On Graco**

**For more than 40 years**, protective coatings contractors have placed their trust in the outstanding quality and durability of Graco equipment. Here are just a few of the reasons why.



# **Superior support and responsive service**

With a global distribution network, you can count on quick turnaround times for replacement parts and service. With Graco's authorized distributors, you have access to experts who understand the unique needs of your business. In addition, Graco has close working relationships with many of the world's leading manufacturers and material suppliers. With Graco, you can expect responsive service and support, as well as the accuracy and reliability you demand from your manufacturing equipment.



# Made with pride

Graco systems are designed, manufactured and built in the United States with global components to Graco's exacting standards. Graco makes significant investments in product development and precision manufacturing to ensure that the products you count on continue to evolve and meet the demands you face in the future.



# **Training is also available**

Graco offers valuable hands-on learning and equipment training at its training centers in the U.S., Belgium and Shanghai, China. Convenient online training courses are also available.

## Trust genuine Graco parts and accessories for all your spray equipment

When you need replacement parts, you could purchase cheaper alternatives. But why risk it? Off-the-shelf parts may hinder performance and possibly even damage your Graco equipment. You invest in Graco equipment because it is superior quality. Graco equipment is designed as a unified system, not as a collection of stand-alone parts. Every part is designed with a careful eye toward the parts it will interact with, and adjusted accordingly. Protect your investment and your future. Trust only genuine Graco parts. For more information on Parts & Accessories for Protective Coatings High Pressure Equipment, refer to brochure 349329.

## **AMERICAS**

#### MINNESOTA

Worldwide Headquarters Graco Inc. 88-11th Avenue N.E. Minneapolis, MN 55413

MAILING ADDRESS

P.O. Box 1441 Minneapolis, MN 55440-1441 Tel: 612-623-6000 Fax: 612-623-6777

#### **EUROPE**

#### BELGIUM

**Graco Distribution BVBA** Industrieterrein-Oude Bunders Slakweidestraat 31 B-3630 Maasmechelen. Belgium

Tel: 32 89 770 700 Fax: 32 89 770 777

#### **ASIA PACIFIC**

#### **AUSTRALIA**

Graco Australia Pty Ltd. Suite 17, 2 Enterprise Drive Bundoora, Victoria 3083

Tel: 61 3 9468 8500 Fax: 61 3 9468 8599

#### CHINA

Graco Hong Kong Ltd. Shanghai Representative Office Building 7 1029 Zhongshan Road South, Huangpu District Shanghai, 200011 The People's Republic of China Tel: 86 21 649 50088 Fax: 86 21 649 50077

#### **IINDIA**

Graco India Pvt Ltd Plot No 295, Udyog Vihar Phase-IV Gurugram - 122015 (Haryana), India Tel: 91 124 6610200 Fax: 91 124 6610201

#### **JAPAN**

Graco K.K. 1-27-12 Hayabuchi Tsuzuki-ku Yokohama City, Japan 2240025 Tel: 81 45 593 7300 Fax: 81 45 593 7301

#### KOREA

Graco Korea Inc. Shinhan Bank Building 4th Floor #1599 Gwanyang-Dong, Dongan-Ku, Anyang-si, Korea 431-060 Tel: 82 31 476 9400 Fax: 82 31 476 9801

©2015-2017 Graco Inc. ELECTRONIC ONLY 349325 Rev. B 09/17 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.



# **Graco Has You Covered**

**Facilities Worldwide for Global Support** 



## **Quality First**

At Graco we pride ourselves on providing best-in-class products. Engineered solutions are manufactured in our own facilities, with the highest standards in the industry. We provide you with world-class customer support and expertise to help solve your application challenges.



## **Global Reach**

Graco has facilities across the globe to provide you with the products and service you need, where you live. Plus, Graco has dedicated field experts in all areas of the world to support the products we sell.



## **Product Capabilities**

Graco has a broad range of products that are engineered and tested to perform in the harshest environments so vou can be certain vour equipment is protected and working at peak performance.

# **Contact us today!**

Call 866-361-5959 to talk with a Graco representative, or visit **www.graco.com** for more information.

